



TECHNICAL DETAILS OF AVI TUBULAR BATTERIES

Model	Capacity *(AH) @ C20	Container	Plate Length (mm)	Tube Length (mm)	No. Of Plates	Dry Weight	Initial Charging Current	Initial Charging Hours
CHAMP 800	65	N100	130	120	5	15.7	3	60
CHAMP 1200	96	N100	130	120	7	21.2	5	60
SUMO 1400	110	JUMBO / N200	145	135	7	25.8	5	60
SUMO 1800	150	JUMBO / N200	145	135	9	32.6	7	60
SUMO 2200	180	JUMBO / N200	145	135	11	38.0	9	60
VICTOR-1200	100	I.T 500 (TALL TUBULAR)	190	180	5	24.5	5	60
VICTOR 1800	150	I.T 500 (TALL TUBULAR)	190	180	7	32.6	7	60
VICTOR 2400	200	I.T 500 (TALL TUBULAR)	190	180	9	41.3	9	60
VICTOR 2000	160	I.T 500 (TALL TUBULAR)	210	200	7	36.7	8	60
VICTOR 1900	155	I.T 500 (TALL TUBULAR)	200	190	7	33.8	7	60
VICTOR 1500	120	I.T 500 (TALL TUBULAR)	230	220	5	29.3	6	60
VICTOR 2200	180	I.T 500 (TALL TUBULAR)	230	220	7	38.3	9	60
VICTOR 2800	240	I.T 500 (TALL TUBULAR)	230	220	9	48.2	12	60

*At 27 degrees C when discharged at C20 upto 1.75Vpc (1.280 sp gr)